


Service Station Layouts

Substr



- | | | |
|---|--|--|
|  <p>1. Waste Vents</p> <ul style="list-style-type: none"> • Pressure Vacuum Vents - OPW A21 Series • Open Vent - OPW 75 |  <p>5. Eliminator Frames</p> <ul style="list-style-type: none"> • Vapor Lines - OPW 233V, 233VM |  <p>8. Submerged Fill Disp. Tubes</p> |
|  <p>2. Cast Iron Manholes</p> <ul style="list-style-type: none"> • 104A - 8", 12", 18" |  <p>6. Overfill Prevention Valves</p> <ul style="list-style-type: none"> • Two-Point - OPW 61SO and 61TNG • Coaxial, Poppered Coaxial - OPW 61SOC, 61SOP • Remote Fill - OPW 61SOR |  <p>9. Tank Gage</p> <ul style="list-style-type: none"> • Fuel Monitoring - OPW 114SW |
|  <p>3. Tight Fill Adaptors and Caps</p> <ul style="list-style-type: none"> • Top Seal - OPW 633T, 633TE |  <p>7. Bell Flow Vent Valve - Extractor Assemblies</p> <ul style="list-style-type: none"> • 2" and 3" Bell Flow Vent Valves - OPW 52VM and 52VML • 30 Minute Warning Bell Flow Vent Valve - OPW 30MV |  <p>10. Observation/Monitoring Manho</p> <ul style="list-style-type: none"> • 104AOW - 8", 12", 18" |
|  <p>4. OPW 1-2100 Spill Containers</p> <ul style="list-style-type: none"> • Thread-on, 5 and 15 gallon • Slip-on, 5 and 15 gallon • Sealable cover, thread-on and slip-on, 5 and 15 gallon • Below grade, 5 and 15 gallon |  <p>11. Emergency Shut-off Valves</p> <ul style="list-style-type: none"> • OPW 10H and 10HP Series • 1 1/2" and 2" sizes available | |

GASOLINE SERVICE STATION EQUIPMENT

J

