

Nozzles

OPW 11 A AUTOMATIC NOZZLES

OPW 11 A Series nozzles are designed with today's consumer in mind. Small, trim, light-in-weight, easy and convenient to use, the OPW 11 A is a rugged performer that offers long life and reliable service.

"Accu-Stop" flow control - allows your customers to top off their tank to the exact amount they want...easy to stop gasoline flow precisely.

Low profile aluminum body - light-weight, easier to handle, provides an attractive, image enhancing appearance. Full hand insulator - protects both nozzle and vehicle, and insulates user's hands.

Hold-open rack is available for full service applications - The one hand control means easy setting to flow rate for customer convenience. Easily replaced spout - simply remove the spout retaining screw. Replacement provides an entirely new outlet check valve. Kits are available from OPW.

Duratuff lever and lever guard - for additional durability in rough handling service.




Blocker on lever guard - to help prevent the nozzle from being jammed into open position with a foreign object. Listed by

Underwriters Laboratories Inc. - for gasoline, 15% ethanol/methanol gasoline blends. Optional spout with Flow Lock - designed to shut-off automatically when the spout is tipped up, limiting spillage. BSPP threads - available by ordering the OPW 11AL. Exclusive two-stage lever assembly - provides a positive shut-off, even if still being held in wide-open position by user. The Optional Message Center is a specially designed 2 piece plastic form that snaps together to provide a long lasting billboard right in your customers' hands! You can have the message area imprinted with a logo by OPW or you can supply custom 1 1/2" labels from a local labeling house. Contact customer service for pricing information.



Materials

Body: aluminum
Lever & lever guard: Duratuff®
Packing: Teflon® impregnated asbestos
Disc: Viton®
Spout: OPW SB & SBP aluminum
Inlet size: 3/4" NPT
Weight: 2.85 lbs. each, 44.90 lbs./case of 15
1.3 kg each, 20.4 kg/case of 15



Optional Message Center


OPW 7H AUTOMATIC SHUT-OFF NOZZLES

For Heavy duty, High Flow Truck, Bus and Fleet Services you operate a full service truck-stop, refuel your own fleet, or manage a cardlock refueling location, the low cost, long life and durability of the OPW 7H high flow nozzle can help increase your productivity, sales and profits.

- Even, smooth spray pattern - minimizes diesel foaming and false shut-offs.
- Extra long anchor spring - keeps the OPW 7H securely in most large fill openings.
- Helps reduce spills - a unique two-stage lever design assures a positive shut-off, even if held wide open.
- Three position hold-open mechanism means easy setting of flow rate.
- Easily replaced spout - simply remove three screws. Replacement kits are readily available from OPW.
- Dash-pot action - for smoother

closing action and reduced line shock.

- Dual poppets - easy to open nozzle against high pressure.
- Available with Flow Lock - designed to shut-off automatically when the spout is tipped up, limiting spillage.
- Listed by Underwriters Laboratories Inc.
- BSPP threads - available with the OPW 7HL



Ordering Specifications

Flow Rate (GPM)	7H	7HL
15	21 010	21 011
20	21 040	21 041
25	21 070	21 071

Equipment Sizes

Flow Rate (GPM)	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
15	15	15	15	15	15	15
20	15	15	15	15	15	15
25	15	15	15	15	15	15

